


贝斯均衡单块 说明书

感谢您使用公司产品，在使用本产品之前请仔细阅读本说明书

操作说明



- 1.直通脚踏开关**
踩下脚踏按键以切换不同的工作状态；
- 2.5段滑动推杆**
调节各频点的增益(-18dB~+18dB)；
- 3.VOLUME旋钮与LED指示灯**
调节总音量，并显示Bass EQ的工作状态，当指示灯亮时为效果开启；
- 4.输入**
1/4"单声道音频接口，信号输入；
- 5.输出**
1/4"单声道音频接口，信号输出；
- 6.电源接口**
9V直流电源(外正内负⊕⌚⊖)；


技术参数

- ◆ 输入：1/4"单声道音接口(阻抗:470kOhms)
- ◆ 输出：1/4"单声道音接口(阻抗:1kOhms)
- ◆ 电源供给：9V直流电流(外正内负⊕⌚⊖)
- ◆ 工作电流：8mA
- ◆ 尺寸：95(L)*45(W)*48(H)mm
- ◆ 重量：245克(带包装)

Bass EQ Pedal Manual

Thanks for purchasing our products, before operating this product, please read the enclosed operating instructions.

Operating Instructions



- 1.True BYPASS Footswitch**
Push down the footswitch to switch between effects and bypass status.
- 2.5-band Slider**
Adjust the level of each frequency band (-18dB~+18dB).
- 3.VOLUME Knob and ON/OFF LED**
Adjust the output level, and indicates effects or bypass status of Bass EQ. When the LED is lit up, the effects is on.
- 4.Input Jack**
1/4"mono audio jack, inputs the signal.
- 5.Output Jack**
1/4"mono audio jack, outputs the signal.
- 6.DC IN Power Jack**
DC 9V regulated AC adapter (Plug polarity is Positive on the barrel and negative in the center ⊕⌚⊖)

Specifications

- ◆ Input: 1/4" Monaural Jack (Impedance: 470K Ohms)
- ◆ Output: 1/4" Monaural Jack (Impedance: 1K Ohms)
- ◆ Power Supply: DC 9V (Plug polarity is Positive on the barrel and negative in the center ⊕⌚⊖)
- ◆ Working Current: 8mA
- ◆ Dimensions: 95(D)*45(W)*48(H)mm
- ◆ Weight: 245g(With box)

尺寸：170*120 mm
正反面，边框线不要印